INDEX

RUBBER CHEMISTRY AND TECHNOLOGY

VOLUME 48, 1975

AUTHOR INDEX

AGEE, R. D., J. L. BROWNLEE, E. SCHARY, AND T. L. TOLBERT, Reinforcement of radial tire casing with Nylon 66 (Abstract), (5) 1094

AHAGON, A., A. N. GENT, H. J. KIM, AND Y. KUMAGAI, Fracture energy of elastomers in Mode I (cleavage) and Mode II (lateral shear), (5) 896

AHNE, H., R. WIEDENMANN, AND W. KLEEBERG, Crosslinking of polyolefins in the presence of new *s*-triazines, (5) 878

ALARIE, Y., E. WILSON, T. CIVIC, J. MAGILL, J. FUNT, C. BARROW, AND J. FROHLIGER, Sensory irritation evoked by polyurethane decomposition products (Abstract), (2) 343

ALLEN, G., P. A. HOLMES, AND D. J. WALSH, Model polystyrene networks, (2) 194

——, see WOLF, F. P., (5) 1018

ANDRIES, J. C., D. B. ROSS, AND H. E. DIEM, Ozone attack and antiozonant protection of vulcanized natural rubber. A surface study by attenuated total reflectance spectroscopy, (1) 41

ARNOLD, R. L., see BOUSTANY, K., (5) 1108

ARRIGHETTI, S., see CESCA, S., (4) 747

ATHEY, R. J., see VAN GULICK, N. M., (5) 1102

BALDUCCI, A., M. BRUZZONE, S. CUCINELLA, AND A. MAZZEI, Advances in the catalysts based on aluminum hydride derivatives for the synthesis of high-*cis* polyisoprene, (4) 736

BARANWAL, K. C., see CARMAN, C. J., (4) 705

BARROW, C., see ALARIE, Y., (2) 343

BAYER, O., The Odyssey of an invention (Charles Goodyear Medal Address—1975), (3) G 73

BEAVAN, S. W., AND D. PHILLIPS, Mechanistic studies on the photooxidation of commercial polybutadiene, (4) 692

BECKER, R. C., see MORGANSTERN, K. H., (5) 1100

BERNSTEIN, B. S., C. KATZ, N. SRINIVAS, AND J. D. HOGAN, Electrochemical treeing in ethylene–propylene rubber compounds (Abstract), (2) 353

BIRKY, M. M., see HILEMAN, F. D., (2) 343

BLACKLEY, D. C., AND M. W. SHEIKH, Particulate reinforcement of polyacrylate elastomers. I. Introduction and preparation of materials, (5) 819

—— and ——, Particulate reinforcement of polyacrylate elastomers. II. Mechanical properties, (5) 830

—— and ——, Particulate reinforcement of polyacrylate elastomers. III. Swelling measurements, (5) 845

BLEYIE, P. L., Influence of morphology and particle size of rubbers in powder form during processing on the mill, (2) 254

BLOW, C. M., H. B. Demirli, AND D. W. SOUTHWART, Anisotropy in molded nitrile rubber, (2) 236

BONICELLI, U., see GIANOTTI, G., (4) 781

BOONSTRA, B. B., H. COCHRANE, AND E. M. DANNENBERG, Reinforcement of silicone rubber by particulate silica, (4) 558

BORGHI, D., see GIANOTTI, G., (4) 781

BOUSTANY, K., AND R. L. ARNOLD, Short-fibers–rubber composites—The comparative properties of treated and discontinuous cellulose fibers (Abstract), (5) 1108

BRAZIER, D. W., AND G. H. NICKEL, Thermoanalytical methods in vulcanizate analysis. I. Differential scanning calorimetry and the heat of vulcanization, (1) 26

—— and ——, Thermoanalytical methods in vulcanizate analysis. II. Derivative thermogravimetric analysis, (4) 661

BROWNLEE, J. L., see AGEE, R. D., (5) 1094

Bruzzone, M., see Balducci, A., (4) 736
——, see Cesca, S., (4) 747
Bryer, R. P., and G. R. Dimeler, Oil requirements of liquid elastomers (Abstract), (2) 346
——, see Dimeler, G. R., (5) 1092
Buchanan, R. A., H. L. Seckinger, W. F. Kwolek, W. M. Doane, and C. R. Russell, Controlling particle size and structure of starch xanthide in elastomer masterbatches (Abstract), (5) 1092
Buckley, D. J., Sr., Failure mode during rapid sinusoidal flexing (Abstract), (2) 357
——, see Cohen, H., (5) 1106
——, see Thaler, W. A., (5) 1105
Bulfield, A. R., Rubber Science Hall of Fame: R. W. Thomson and J. B. Dunlop, (1) G 43
Bullman, G. W., see Wood, L. A., (2) 154
Burleigh, J. E., see Uraneck, C. A., (4) 728
Bywater, S., see Roovers, J. E. L., (5) 1070

Carman, C. J., and K. C. Baranwal, Molecular structure of elastomers determined with carbon-13 NMR, (4) 705
—— and C. E. Wilkes, Quantitative measurement of isomer composition in polypentenamer using carbon-13 nuclear magnetic resonance, (2) 329
Carpenter, R. L., see Kramer, O., (2) 164
Caruso, P. P., see Van Gulick, N. M., (5) 1102
Cesca, S., S. Arrighetti, A. Priola, P. V. Duranti, and M. Bruzzone, Terpolymers of ethylene, propylene, and tricyclo[5.2.1.$0^{2,6}$]deca-2,5,8-triene, (4) 747
Charrier, J.-M., N. V. Hien, R. H. Marchessault, and F. H. Moy, Structure and mechanical properties of biaxially stretched crystallizing rubber (Abstract), (5) 1093
Chen, I.-J., see Reber, D., (5) 1108
Chen, R. Y. S., C. U. Yu, and J. E. Mark, Stress–strain isotherms and stress–temperature coefficients of poly(dimethylsiloxane) networks in compression, (2) 176
Chien, W. P., see Seader, J. D., (2) 341
Chirico, V. E., see Dizon, E. S., (5) 1090
——, see Ulmer, J. D., (4) 592
Chung, D. A., see Rogers, T. H., (5) 1101
Civic, T., see Alarie, Y., (2) 343
Cochrane, H., see Boonstra, B. B., (4) 558
Cohen, H., J. A. Rae, and D. J. Buckley, Sr., High-molecular-weight, high-unsaturation isobutylene–conjugated-diene copolymers, a new family of elastomers. II. Properties and performance (Abstract), (5) 1106
Coleman, J. F., Castable reinforced elastomers. II. New Processing methods (Abstract), (5) 1112
Collins, E. A., see Nakajima, N., (1) 69, (4) 615
Conant, F. S., Using the SI system of units, (1) 1
Conway, H. F., and V. E. Sohns, Starch-encased powdered rubber—Pilot-plant production (Abstract), (2) 338
Cotton, G. R., Influence of carbon black on processability of rubber stocks. I. Bound rubber formation, (4) 548
Crane, G., and E. L. Kay, Scrap tire disposal process, (1) 50
——, ——, and L. B. Wakefield, Hydrocarbon tackifying resins *ex* scrap tires (Abstract), (2) 338
——, J. W. Fieldhouse, and E. L. Kay, Antioxidant activity of depolymerized scrap rubber, (1) 62
Crisostomo, L. S., Homogeneity-of-cure test (Abstract), (5) 1113
Critchfield, F. E., see Gerkin, R. M., (5) 972
Cucinella, S., see Balducci, A., (4) 736
Cunningham, W. K., and D. R. Hart, Evaluation of Resotropin as an adhesion promoter for use with brassed steel wire cord (Abstract), (2) 346
——, see Hart, D. R., (5) 1103

D'Amico, J. J., K. T. Potts, J. Kane, D. McKeough, and K. F. Moschner, Electron-impact-induced fragmentation of N-(substituted-thio)phthalimides. A rationalization fo. their prevulcanization inhibition, (4) 790
Dannenberg, E. M., The effects of surface chemical reactions on the properties of filler-reinforced rubbers, (3) 410
——, see Boonstra, B. B., (4) 558
Dawson, R. L., see Stewart, C. W., Sr., (1) 132

DEMIRLI, H. B., see BLOW, C. M., (2) 236
DEVRIES, K. L., Free radicals generated in rubber during fracture, (3) 445
DIEM, H. E., see ANDRIES, J. C., (1) 41
DIMELER, G. R., AND R. P. BRYER, The effect of combined sulfur in extender oils on vulcanizate properties (Abstract), (5) 1092
——, see BRYER, R. P., (2) 346
DIZON, E. S., A. E. HICKS, AND V. E. CHIRICO, Carbon-black reinforcement in fatigue and cut growth (Abstract), (5) 1090
——, E. J. MICEK, AND C. E. SCOTT, Performance characteristics of present-day tread blacks (Abstract), (2) 339
——, see ULMER, J. D., (4) 592
DJIAUW, L. K., AND A. N. GENT, Elasticity of uncrosslinked rubbers, (5) 995
DOANE, W. M., see BUCHANAN, R. A., (5) 1092
DUNN, J. R., see PFISTERER, (2) 356
DURANTI, P. V., see CESCA, S., (4) 747

EDGERTON, N. W., see FISHER, R. G., (2) 350
EDWARDS, D. C., Network formation and reinforcement studies with terminally brominated polybutadiene, (2) 203
EICHINGER, B. E., see LEUNG, Y. K., (1) 108, 119
EINHORN, I. N., see HILEMAN, F. D., (2) 343
——, see PACKHAM, S. C., (2) 342
EVANS, C. W., Powdered polymers at work (Abstract), (5) 1099

FERRY, J. D., see KRAMER, O., (2) 164, (5) 1004
——, see MITSUDA, Y., (5) 1035
FETTERS, L. J., see MORTON, M., (3) 359
FIELDHOUSE, J. W., see CRANE, G., (1) 62
FINELLI, A. F., see ROGERS, T. H., (5) 1101
FISHER, R. G., AND N. W. EDGERTON, Elastomers in solid dielectric wire and cable applications (Abstract), (2) 350
FISCHER, T. M., JR., The role of thermosetting elastomers in automatic wiring (Abstract), (2) 353
FLEIGE, S., see SCHEELE, W., (5) 889
FLORY, P. J., Molecular configuration in bulk polymers, (3) 513
FORSTER, E. O., see SMITH, W. C., (2) 351
FROHLIGER, J., see ALARIE, Y., (2) 343
FUJITA, H., see KATO, H., (1) 19
——, see TSUJI, T., (4) 765
FUNT, J. M., AND J. H. MAGILL, Flame spread models as predictors of large fire behavior (Abstract), (2) 345
——, see ALARIE, Y., (2) 343
FURUKAWA, J., E. KOBAYASHI, K. URATANI, Y. ISEDA, J. UMEMURA, AND T. TAKENAKA, Infrared absorption spectra of alternating copolymers of butadiene with acrylonitrile and deuterated analogs, (4) 719

GALLOWAY, F. M., Automated hose production—Is it for you? (Abstract), (5) 1096
GENT, A. N., see AHAGON, A., (5) 896
——, see DJIAUW, L. K., (5) 995
GERKIN, R. M., F. E. CRITCHFIELD, W. A. MILLER, R. ROBERTS, AND C. G. SEEFRIED, JR., Recycling scrap crosslinked urethane polymers, (5) 972
GIANOTTI, G., U. BONICELLI, AND D. BORGHI, Dilute-solution properties of *trans*-Polypentenamer: $[\eta]$–M relations and molecular conformations, (4) 781
GNÖRICH, W., AND K. A. GROSCH, The friction of polymers on ice, (4) 527
GOLUB, M. A., AND M. S. HSU, Nuclear magnetic resonance study of thermal oxidation of polyisoprene, (5) 953
GRAESSLEY, W. W., Statistical mechanics of random coil networks, (5) 1008
GRANT, G. D., Trends in conveyor belt carcass materials (Abstract), (5) 1096
GRAS, D., Continuous processing of rubber compounds (Abstract), (5) 1098
GRASSIE, N., AND A. HEANEY, Thermal degradation of copolymers of butadiene and acrylonitrile, (4) 678
GRIMM, D. C., see HORVATH, J. W., (2) 337
GROSCH, K. A., see GNÖRICH, W., (4) 527
GROSS, D., Degradation of vulcanizates and their identification by IR spectrometry, (2) 289

Gunberg, P. F., see Van Buskirk, P. R., (4) 577
Gursky, L., F. J. Masiello, and A. J. Wallace, Improved chlorinated butyl blend compounds for tire sidewalls (Abstract), (5) 1112

Hale, K. L., J. R. West, and C. E. McCormick, The contribution of carbon black type to skid and treadwear resistance (Abstract), (5) 1091
Hart, D. R., and W. K. Cunningham, The Phenotropins—Novel methylene donors (Abstract), (5) 1103
——, see Cunningham, W. K., (2) 346
Harwood, H. J., and T. Suzuki, Characterization of elastomer structure by high-field NMR spectroscopy (Abstract), (5) 1109
Haxo, H. E., Jr. and P. K. Mehta, Ground rice-hull ash as a filler for rubber, (2) 271
Heaney, A., see Grassie, N., (4) 678
Hedaya, E., see Peters, E. N., (1) 14
Hertel, D. L., and C. K. Oliver, A practical approach to injection molding using an Instron capillary rheometer (Abstract), (2) 355
Hicks, A. E., see Dizon, E. S., (5) 1090
Hien, N. V., see Charrier, J.-M., (5) 1093
Hileman, F. D., K. J. Voorhees, L. H. Wojcik, M. M. Birky, P. W. Ryan, and I. N. Einhorn, Pyrolysis of a flexible urethane foam (Abstract), (2) 343
Hogan, J. D., see Bernstein, B. S., (2) 353
Holmes, P. A., see Allen, G., (2) 194
Holownia, B. P., Effects of carbon black on the Poisson ratio of elastomers, (2) 246
Hopwood, J. E., and W. C. Neller, Microwave preheating of conveyor belting (Abstract), (5) 1098
Horvath, J. W., D. C. Grimm, and J. A. Stevick, Improved NBR service performance with polymerization-stabilized nitrile rubbers (Abstract), (2) 337
Howard, W. S., and C. R. Wilder, Effect of curing temperature on the tread wear of synthetic rubber tread stocks (Abstract), (2) 356
Hsu, M. S., see Golub, M. A., (5) 953

Iseda, Y., see Furukawa, J., (4) 719

Jacobs, H. L., see Newell, W. W., (5) 1099
Johnson, P. H., see Stacy, C. J., (4) 538
Johnson, P. R., R. Pariser and J. J. McEvoy, Elastomers and flammability (Abstract), (2) 340
——, see Stewart, C. W., Sr., (1) 132

Kalfayan, S. H., R. H. Silver, and A. A. Mazzeo, Accelerated heat-aging studies on fluorosilicone rubber, (5) 944
Kane, J., see D'Amico, J. J., (4) 790
Kapur, R., R. Shelton, and J. L. Koenig, Fourier transform infrared studies of vulcanization of *cis*-1,4-polybutadiene (Abstract), (2) 348
Kato, H., and H. Fujita, Some novel systems for crosslinking of polychloroprene, (1) 19
Katritzky, A. R., and D. E. Weiss, Carbon-13 nuclear magnetic resonance spectroscopy of polymers. Part IV. Peak assignment for styrene–butadiene copolymers, (5) 1044
—— and ——, Carbon-13 nuclear magnetic resonance spectroscopy of polymers. Part V. Monomer sequence in styrene–butadiene copolymers, (5) 1055
Katz, C., see Bernstein, B. S., (2) 353
Kawakami, J. H., see Peters, E. N., (1) 14
Kay, E. L., see Crane, G., (1) 50, 62, (2) 338
——, see Lawson, D. F., (1) 124
Keeley, F. W., D. R. Luh, and R. L. Morgan, New EPDM developments for electrical industry applications (Abstract), (2) 354
Kim, H. J., see Ahagon, A., (5) 896
Kleeberg, W., see Ahne, H., (5) 878
Klingensmith, W., The use of tallow fatty acids in rubber (Abstract), (2) 348
Kobayashi, E., see Furukawa, J., (4) 719
Koch, R. B., High-pressure thermoplastic hose replaces rubber (Abstract), (5) 1095
Koenig, J. L., see Kapur, R., (2) 348
Kotaka, T., and J. L. White, Thin-layer chromatographic separations of butadiene–styrene copolymers on the basis of composition and molecular weight, (2) 310
Kramer, O., R. L. Carpenter, V. Ty, and J. D. Ferry, Entanglement networks of 1,2-polybutadiene crosslinked in states of strain. I. Crosslinking at 0°, (2) 164

——, AND J. D. FERRY, Entanglement networks of 1,2-polybutadiene crosslinked in states of strain. II. Application of the Mooney–Rivlin equation to networks crosslinked at 0°C, (5) 1004
KRAUS, G., see STACY, C. J., (4) 538
KRISHEN, A., AND R. G. TUCKER, Quantitative determination of the polymeric constituents in compounded cured stocks by Curie-point pyrolysis–gas chromatography, (1) 97
KUMAGAI, Y., see AHAGON, A., (5) 896
KWEI, T. K., T. NISHI, AND R. F. ROBERTS, A study of compatible polymer mixtures, (2) 218
KWIATKOWSKI, G. T., see PETERS, E. N., (1), 14
KWOLEK, W. F., see BUCHANAN, R. A., (5) 1092

LAMOND, T. G., see SIRCAR, A. K., (1) 79, 89, (2) 301, (4) 631, 640, 653
LAWSON, D. F., E. L. KAY, and D. T. ROBERTS, JR., Mechanism of smoke inhibition by hydrated fillers, (1) 124
LEICHT, J. T., see SWANSON, J. W., (2) 337
LENTZ, C. W., see POLMANTEER, K. E., (5) 795
LEO, T. J., Greater profitability in the manufacture of belts and hose by the use of high-quality polymeric dispersions of critical chemicals (Abstract), (5) 1093
LEUNG, Y.-K., AND B. E. EICHINGER, Gas–liquid chromatography on polymers. I. Polyisobutylene–hydrocarbons at 25°C, (1) 108
—— and ——, Gas–liquid chromatography on polymers. II. Temperature coefficients for polyisobutylene–hydrocarbons, (1) 119
LUH, D. R., see KEELEY, F. W., (2) 354

MAGILL, J. H., see ALARIE, Y., (2) 343
——, see FUNT, J. M., (2) 345
MARCHESSAULT, R. H., see CHARRIER, J.-M., (5) 1093
MARK, H., Otto Bayer, Charles Goodyear Medalist—1975, (3) G 70
MARK, J. E., The constants $2C_1$ and $2C_2$ in phenomenological elasticity theory and their dependence on experimental variables, (3) 495
——, see CHEN, R. Y. S., (2) 176
——, see YU, C. U., (2) 186
MASIELLO, F. J., see GURSKY, L., (5) 1112
MAZZEI, A., see BALDUCCI, A., (4) 736
MAZZEO, A. A., see KALFAYAN, S. H., (5) 944
MCCALL, D. W., Nuclear magnetic resonance studies of molecular relaxation mechanisms in polymers (Abstract), (5) 1109
MCCORMICK, C. E., see HALE, K. L., (5) 1091
MCEVOY, J. J., see JOHNSON, P. R., (2) 340
MCKEOUGH, D., see D'AMICO, J. J., (4) 790
MCNEIL, D. W., see PETERS, E. N., (1) 14
MEHTA, P. K., see HAXO, H. E., (2) 271
MEISSNER, B., Theory of bound rubber, (5) 810
MEREDITH, R. J., Microwave energy for high-speed, efficient vulcanization of extruded rubber (Abstract), (5) 1100
METZGER, S. H., JR., AND D. J. PREPELKA, Progress in RIM technology (Abstract), (5) 1103
MICEK, E. J., see DIZON, E. S., (2) 339
MICKLEY, A. S., A user looks at rubber-insulated cables, 15 kV and above (Abstract), (2) 350
MILLER, W. A., see GERKIN, R. M., (5) 972
MILLER, W. G., AND Z. VEKSLI, The use of stable free radicals to determine motion in polymeric systems, (5) 1078
MITSUDA, Y., J. L. SCHRAG, AND J. D. FERRY, Estimation of long-chain branching in ethylene–propylene terpolymers from infinite-dilution viscoelastic properties, (5) 1035
MONTE, S. J., AND G. SUGERMAN, A new coupling agent for extenders, fillers, and reinforcements used in polymers (Abstract), (5) 1091
MORGAN, A. W., AND J. H. OREM, Testing anomalies in polymer fire retardance (Abstract), (2) 344
MORGAN, R. L., see KEELEY, F. W., (2) 354
MORGANSTERN, K. H., AND R. C. BECKER, The technology and economics of radiation curing (Abstract), (5) 1100
MORTON, M., AND L. J. FETTERS, Anionic polymerization of vinyl monomers, (3) 359
——, AND D. C. RUBIO, Synthesis and properties of uniform polyisoprene networks (Abstract), (5) 1104

——, J. P. Rupert, and E. R. Santee, 300 MHz NMR chain-structure analysis of high-*cis* 1,4 lithium polyisoprene (Abstract), (5) 1110
Moschner, K. F., see D'Amico, J. J., (4) 790
Moy, F. H., see Charrier, J.-M., (5) 1093
Murakami, K., Recent chemorheological studies on rubber vulcanizates, (5) 913
——, see Tamura, S., (2) 141

Nakajima, N., and E. A. Collins, A master curve for amorphous elastomers derived from small and large deformation using various instruments, (1) 69
—— and ——, Capillary rheometry of carbon-black-filled butadiene–acrylonitrile copolymers, (4) 615
Naoki, M., and T. Nose, Strain dependence of the glass transition point of chlorinated polyethylene vulcanizates, (4) 623
Neller, W. C., see Hopwood, J. E., (5) 1098
Newell, W. W., J. P. Porter, and H. L. Jacobs, The power integrator—A new instrument for controlled mixing (Abstract), (5) 1099
Nickel, G. H., see Brazier, D. W., (1) 26, (4) 661
Nishi, T., see Kwei, T. K., (2) 218
Noble, M. G., Silicone rubber insulation for Class IE electric cables (Abstract), (2) 355
Nose, T., see Naoki, M., (4) 623

Oliver, C. K., see Hertel, D. L., (2) 355
Orem, J. H., see Morgan, A. W., (2) 344
Oswald, A. A., see Zapp, R. L., (5) 860

Packham, S. C., J. H. Petajan, and I. N. Einhorn, The physiological response to smoke and combustion products (Abstract), (2) 342
Palmgren, H., Processing conditions in the batch-operated internal mixer, (3) 462
Pariser, R., see Johnson, P. R., (2) 340
Pearson, C. J., see Rogers, T. H., (5) 1101
Petajan, J. H., see Packham, S. C., (2) 342
Peters, E. N., E. Hedaya, J. H. Kawakami, G. T. Kwiatkowski, and D. W. McNeil, D_2-*meta*-carborane-siloxane elastomers, (1) 14
Petersen, K. C., and J. L. Sullivan, An advance in elastomer tackification (Abstract), (5) 1093
Pfisterer, H. A., and J. R. Dunn, Assessing the performance of oil-resistant vulcanizates at high temperatures (Abstract), (2) 356
Phillips, D., see Beavan, S. W., (4) 692
Piccoli, D. E., Hose design for unusual hose applications (Abstract), (5) 1095
Polmanteer, K. E. and C. W. Lentz, Reinforcement studies—Effect of silica structure on properties and crosslink density, (5) 795
Porter, J. P., see Newell, W. W., (5) 1099
Potts, K. T., see D'Amico, J. J., (4) 790
Prepelka, D. J., see Metzger, S. H., Jr., (5) 1103
Priola, A., see Cesca, S., (4) 747

Rae, J. A., see Cohen, H., (5) 1106
Reber, D., I.-J. Chen, and K. J. Siwiecki, Relationship between machine operating variables and temperature of elastomer entering the mold on a coaxial screw–pot injection molding machine (Abstract), (5) 1108
Ridland, J. J., J. Walker, and R. J. Weir, New compounding techniques for improved hose performance (Abstract), (5) 1094
Rienzner, H. J., Recent developments in the use of multistation injection molding machines, (2) 263
Roberts, D. T., Jr., see Lawson, D. F., (1) 124
Roberts, R., see Gerkin, R. M., (5) 972
Roberts, R. F., see Kwei, T. K., (2) 218
Rodger, E. R., and H. S. Roebuck, Improved processing economics through scorch control (Abstract), (5) 1108
Roebuck, H. S., see Rodger, E. R., (5) 1108
Rogers, T. H., A. F. Finelli, C. J. Pearson, and D. A. Chung, Flex requirement of cast urethane elastomers for solid industrial tires (Abstract), (5) 1101
Roovers, J. E. L., and S. Bywater, The reaction of *t*-butyllithium with styrene and isoprene. A comparison of chain initiation with the isomers of butyllithium, (5) 1070

Ross, D. B., see Andries, J. C., (1) 41
Ross, J. A., Contrasts in European and American hose technology, (Abstract) (5) 1094
Roth, F. L., see Wood, L. A., (2) 154
Rubio, D. C., see Morton, M., (5) 1104
Rupert, J. P., see Morton, M., (5) 1110
Russell, C. R., see Buchanan, R. A., (5) 1092
Ryan, P. W., see Hileman, F. D., (2) 343

Santee, E. R., see Morton, M., (5) 1110
Saxon, R., see Singh, A., (2) 348
Schaefer, J., and E. O. Stejskal, Carbon-13 NMR studies of carbon-black-filled elastomers (Abstract), (5) 1109
Schary, E., see Agee, R. D., (5) 1094
Scheele, W., and S. Fleige, The vulcanization of highly elastic polymers. 81. Sulfur vulcanization of ethylene–propylene terpolymers containing varying amounts of double bonds, (5) 889
Schollenberger, C. S., and F. D. Stewart, Thermoplastic polyurethane elastomer uv stabilization (Abstract), (5) 1101
Schrag, J. L., see Mitsuda, Y., (5) 1035
Scott, C. E., see Dizon, E. S., (2) 339
Seader, J. D., and W. P. Chien, Physical characteristics of smoke development (Abstract), (2) 341
Seckinger, H. L., see Buchanan, R. A., (5) 1092
Seefried, C. G., see Gerkin, R. M., (5) 972
Semin, R. E., New automotive power transmission belt concepts (Abstract), (5) 1096
Sheard, E. A., A new composite tire for moderate-speed applications (Abstract), (5) 1093
Sheikh, M. W., see Blackley, D. C., (5) 819, 830, 845
Shelton, R., see Kapur, R., (2) 348
Siebert, A. R., Castable reinforced elastomers. I. Material properties (Abstract), (5) 1111
Silver, D. A., An improved free-stripping tape insulation shield EPR-insulated high-voltage power cable (Abstract), (2) 351
Silver, R. H., see Kalfayan, S. H., (5) 944
Singh, A., and R. Saxon, Improved moisture resistance in polyester-based polyurethanes (Abstract), (2) 348
Sircar, A. K., and T. G. Lamond, Strain-dependent dynamic properties of carbon-black reinforced vulcanizates. I. Individual elastomers, (1) 79
—— and ——, Strain-dependent dynamic properties of carbon-black reinforced vulcanizates. II. Elastomer blends, (1) 89
—— and ——, Identification of elastomers in tire sections by total thermal analysis. I. Tread and black sidewall, (2) 301
—— and ——, Identification of elastomers in tire sections by total thermal analysis. II. White sidewall compounds of EPDM and blends, (4) 631
—— and ——, Identification of elastomers in tire sections by total thermal analysis. III. White sidewall compounds of neoprene rubber blends, (4) 640
—— and ——, Identification of elastomers in tire sections by total thermal analysis. IV. Innerliner, (4) 653
Siwiecki, K. J., see Reber, D., (5) 1108
Smith, W. C., and E. O. Forster, Effect of composition on the dielectric properties of ethylene–propylene rubber base compounds (Abstract), (2) 351
Sohns, V. E., see Conway, H. F., (2) 338
Southwart, D. W., see Blow, C. M., (2) 236
Srinivas, N., see Bernstein, B. S., (2) 353
Stacy, C. J., P. H. Johnson, and G. Kraus, Effect of carbon black structure aggregate size distribution on properties of reinforced rubber, (4) 538
Stanhope, H. W., Polyester fabric reinforcement for conveyor belts (Abstract), (5) 1092
Stejskal, E. O., see Schaefer, J., (5) 1109
Stevick, J. A., see Horvath, J. W., (2) 337
Stewart, C. W., Sr., R. L. Dawson, and P. R. Johnson, The effect of compounding variables on the rate of heat and smoke release from polychloroprene foam, (1) 132
Stewart, F. D., see Schollenberger, C. S., (5) 1101
Stockmayer, W. H., Paul J. Flory, 1974 Nobel Prize Winner, (1) G 38
Sugerman, G., see Monte, S. J., (5) 1091
Sullivan, J. L., see Petersen, K. C., (5) 1093
Suzuki, T., see Harwood, H. J., (5) 1109

Swaim, B. C., Corona detection in molded instrument transformers (Abstract), (2) 353
Swanson, J. W., J. T. Leicht, and R. L. Wegener, Silicone rubber in powder form (Abstract), (2) 337

Takenaka, T., see Furukawa, J., (4) 719
Tamura, S., and K. Murakami, Chemorheology of irradiation-cured natural rubbers: 1. Stress relaxation mechanism for various curing systems in natural rubber at high temperature, (2) 141
Thaler, W. A., and D. J. Buckley, Sr., High-molecular-weight, high-unsaturation isobutylene–conjugated-diene copolymers, a new family of elastomers. I. Synthesis (Abstract), (5) 1105
Thirion, P., Viscoelastic properties of rubber networks, (5) 981
Thomas, A. G., Factors influencing the strength of rubbers, (5) 902
Tolbert, T. L., see Agee, R. D., (5) 1094
Tsuji, T., and H. Fujita, Excluded-volume effects in dilute polymer solutions. V. Butyl rubber in various solvents, (4) 765
Tucker, R. G., see Krishen, A., (1) 97
Turetzky, S. B., see Van Buskirk, P. R., (4) 577
Ty, V., see Kramer, O., (2) 164

Ulmer, J. D., V. E. Chirico, and E. S. Dizon, Application of an equivalent strain at equal stress principle to the dynamic hysteresis of carbon-black-loaded and oil-extended rubber, (4) 592
Umemura, J., see Furukawa, J., (4) 719
Uraneck, C. A., and J. E. Burleigh, Modification of emulsion polymerization with blends of mercaptans, (4) 728
Uratani, K., see Furukawa, J., (4) 719

Van Buskirk, P. R., S. B. Turetzky, and P. F. Gunberg, Paractical parameters for mixing, (4) 577
Van Gulick, N. M., J. J. Verbanc, P. P. Caruso, and R. J. Athey, Coordination complexes of methylene dianiline—Chemistry and applications (Abstract), (5) 1102
Veksli, Z., see Miller, W. G., (5) 1078
Verbanc, J. J., see van Gulick, N. M., (5) 1102
Von Wald, J. L., A technological forecast on future rubber processing (Abstract), (5) 1096
Voorhees, K. J., see Hileman, F. D., (2) 343

Wakefield, L. B., see Crane, G., (2) 338
Walker, J., see Ridland, J. J., (5) 1094
Wallace, A. J., see Gursky, L., (5) 1112
Walsh, D. J., see Allen, G., (2) 194
Wegener, R. L., see Swanson, J. W., (2) 337
Weir, R. J., see Ridland, J. J., (5) 1094
Weiss, D. E., see Katritzky, A. R., (5) 1044, 1055
West, J. R., see Hale, K. L., (5) 1091
White, J. L., see Kotaka, T., (2) 310
Wiedenmann, R., see Ahne, H., (5) 878
Wilder, C. R., see Howard, W. S., (2) 356
Wilkes, C. E., see Carman, C. J., (2) 329
Wilson, E., see Alarie, Y., (2) 343
Wojcik, L. H., see Hileman, F. D., (2) 343
Wolf, F. P., and G. Allen, The energetic contribution to rubber elasticity in the range of small uniaxial compression and moderate elongation, (5) 1018
Wood, L. A., G. W. Bullman, and F. L. Roth, Long-time creep in a pure-gum rubber vulcanizate: Influence of humidity and atmospheric oxygen, (2) 154

Yingling, W. P., New horizons in heat belts (Abstract), (5) 1098
Yu, C. U., and J. E. Mark, Evaluation of the theories of rubberlike elasticity using swollen networks crosslinked at different degrees of dilution, (2) 186
——, see Chen, R. Y. S., (2) 176

Zapp, R. L., and A. A. Oswald, Radiation-induced crosslinking of chlorobutyl and polydiene elastomers. Promotion by polythiols, (5) 860

SUBJECT INDEX

Abrasion, see also Tread wear
  and crack growth, (5) 902
  and tearing energy, (5) 902
  mechanism of, (5) 902
  of rubber by blade abrader, (5) 902
Abrasion resistance, effect of promoters, (3) 410
  of filler-reinforced vulcanizates, (3) 410
  of polyurethane elastomer, (3) G73
  of SBR–BR treads, effect of curing temperature on, (2) 356
  of silica–rubber systems, (3) 410
Abstracts of papers presented at Rubber Division meetings, (2) 337, (5) 1090
Accelerators for polychloroprene vulcanization, (1) 19
Acids, tallow fatty, use in rubber, (2) 348
Acrylic rubber, see Polyacrylate
Acrylonitrile–butadiene copolymer, see Nitrile rubber
  alternating, (4) 719
Acrylonitrile–butadiene–styrene resin (ABS), modifiers for polymerization, (4) 728
  photooxidation of, (4) 692
Adhesion, of polyacrylate to glass, (5) 830
  of rubber to metal and glass, (3) G73
  promoters for rubber-to-cord, (5) 1103
  Resotropin as promoter for, to wire cord, (2) 346
Alanes, (4) 736
Alkali metals as polymerization initiators, (3) 359
Alkyllithium, see Butyllithium and Organolithium compounds
Alternating copolymers of butadiene and acrylonitrile, (4) 719
Alumina trihydrate for smoke inhibition, (1) 124
Aluminum hydride derivatives, as diene polymerization catalysts, (4) 736
Amines for crosslinking of terminally brominated BR, (2) 202
γ-Aminopropyltriethoxysilane, surface treatment of glass by, (5) 819
2-Amino-1,3,4-thiadiazole as vulcanization accelerator for polychloroprene, (1) 19
Amorphous elastomers, master deformation curves for, (1) 69
Analysis, of degraded vulcanizates by ir spectroscopy, (2) 289
  of SBR by thin-layer chromatography, (2) 310
  of tire components, (2) 301, (4) 631, 640, 653
  of vulcanizates, by Curie-point pyrolysis–gas chromatography, (1) 97
  of vulcanizates, by thermoanalytical methods, (1) 26, (2) 301, (4) 631, 640, 653, 661
N-4-Anilinomethacrylamide, as polymer-bound antioxidant in NBR, (2) 337
Anionic polymerization, chain-end structure, (3) 359
  effect of solvent, (3) 359
  experimental technique, (3) 359
  grafting to carbon black by, (3) 410
  high-vacuum technique, (3) 359
  initiation methods, (3) 359
  kinetics, (3) 359
  mechanism, (3) 359
  molecular weight distribution in, (3) 359
  purification of materials for, (3) 359
  of dienes, (3) 359
  of vinyl monomers, (3) 359
  review, (3) 359
  to prepare block copolymer, (3) 359
  with alkali metals, (3) 359
  with alkyllithium, (3) 359
Anisotropy, in molded NBR, (2) 236
  studied by linear swelling, (2) 236
Antioxidants, as components of uv stabilizers for polyurethanes, (5) 1101
  copolymerized in NBR, (2) 337
  depolymerized scrap rubber as, (1) 62
  in hose manufacture, (5) 1094
Antiozonants, mechanism of protection by, (1) 41
  protection of vulcanizates by, (1) 41
Attenuated total reflectance spectroscopy, in study of ozone attack on rubber vulcanizates, (1) 41
Autoxidation, of polyisoprene, NMR study, (5) 953

Balata, NMR spectrum, (5) 953
Banbury, see Internal mixers
Belts, automotive, design, (5) 1097
  conveyor, carcass materials, (5) 1097
  dispersions in manufacture of, (5) 1093
  for handling hot material, (5) 1098
  microwave heating in manufacture of, (5) 1098
  polyester fabric in, (5) 1092
Biographical Sketches, Bayer, O., (3) G70
  Dunlop, J. B. (1) G43
  Flory, P. J., (1) G38
  Kastein, B., (1) G25
  Thomson, R. W., (1) G43
Blends, of chlorinated butyl in tire sidewalls, (5) 1112
  of compatible polymers, (2) 218
  of NR and BR, vulcanization, (1) 26

of rubber, analysis by ^{13}C NMR, (4) 705
of rubbers, analysis by pyrolysis–GC, (1) 97
of rubbers, dynamic properties, (1) 89
of rubbers, friction on ice, (4) 527
Block copolymers, by anionic polymerization, (3) 359
Book reviews, "Antioxidants", (3) G82
"Dictionary of Rubber", (2) G55
"Injection Molding of Rubber", (2) G56
"Man-made Fibres", (4) G95
"Statistical Design of Fatigue Experiments", (5) G103
"The Friction of Pneumatic Tyres", (5) G103
Bound rubber, effect of coupling agents on, (3) 410
effect of heat treatment on, (3) 410
effect on processability, (4) 548
effect of promoters on, (3) 410
in carbon-black–rubber systems, (3) 410
in SBR–carbon-black compounds, (4) 577
in silica–rubber systems, (3) 410
in silica–silicone systems, (4) 558
on carbon black, (5) 810
on silica, (5) 810
theory, (5) 810
Branching, long-chain, (5) 1035
Butadiene–acrylonitrile copolymer, see Nitrile rubber
Butadiene Styrene rubber, see Styrene butadiene rubber
1,4-Butanedithiol in radiation cure of CIIR, (5) 860
1-Butanethiol in radiation cure of CIIR, (5) 860
Butyllithium, effect of butoxylithium impurity, (5) 1070
initiation of polymerization, (5) 1070
isomers in polymerization, (5) 1070
reaction with styrene and isoprene, (5) 1070
Butyl rubber (IIR), Banbury mixing time, (3) 410
brominated, identification in blends, (4) 653
carbon black reinforcement, (3) 410
chlorinated, in sidewall blends, (5) 1112
dilute-solution properties, (4) 765
effect of promoter on reinforcement, (3) 410
identification in blends, (4) 653
radiation curing of, (5) 860
silica reinforcement, (3) 410
structure of, (4) 765
thermal analyses of, (4) 661
theta solvents for, (4) 765

C_2 Values, for poly(dimethylsiloxane) networks, (2) 176
review, (3) 495
Cable, see also Wire
rubber insulated, (2) 350
shield design for high voltage, (2) 351
silicone rubber insulation for, (2) 355
Capillary rheometer, and master curve, (1) 69
use for carbon-black-filled NBR, (4) 615
Carbon black, adsorption of polymer on, (4) 548, (5) 810
aggregates, polydispersity of, (4) 538
and rubber mixtures, heat treatment, (3) 410
crystallinity by X-ray diffraction, (3) 410
effect of aggregate size on rubber properties, (4) 538
effect of heating on structure, (3) 410
effect of, on rheology of NBR, (4) 615
effect on fatigue and cut growth, (5) 1090
effect on friction of rubber on ice, (4) 527
effect on Poisson ratio of elastomers, (2) 246
effect on tire properties, (5) 1091
-filled SBR, dynamic properties, (4) 592
functional group modification, (3) 410
grafting of polymers to, (3) 410
graphitized, in SBR, (4) 548
in capillary rheometry, (4) 615
in depolymerized scrap rubber, (1) 50
in rubber mixing, (4) 577
in vulcanizates, strain-dependent dynamic properties, (1) 79, 89
interaction with rubber, NMR study, (5) 1109
particle aggregation, (1) 79, 89
performance of present-day, (2) 339
reflocculation, (3) 410
reinforcement by, (3) 410
reinforcement in terminally unsaturated BR networks, (2) 202
–SBR masterbatches, bound rubber, (4) 548
structure, effect on properties, (4) 538
surface-bound hydrogen, (3) 410
surface-modified, (3) 410
surface oxidation, (3) 410
surface treatment, (3) 410
Carbon gel, see Bound rubber
Carbon monoxide, physiological response to, (2) 342
Carborane elastomers, (1) 14
Carborane–siloxane elastomers, (1) 14
Cationic polymerization, effect of solvent and temperature, (5) 1105
of isobutylene with isoprene or cyclopentadiene, (5) 1105
Cellulose fibers, short, as reinforcing agents, (5) 1108
Cetyltrimethylammonium bromide, see CTAB
Chain scission, during fracture, (3) 445
of natural-rubber vulcanizates, (2) 141
Chain transfer, in anionic polymerization, (3) 359
in emulsion polymerization, by mercaptan blends, theory, (4) 728

Characterization of elastomers by ^{13}C NMR, (4) 705
Char promotion in combustion of polychloroprene foam, (1) 132
Chemical promoters, see Promoters and Coupling agents
Chemorheology, of irradiation-cured NR, (2) 141, 154
of rubber vulcanizates, (5) 913
of uncrosslinked linear polymers, (5) 913
Chlorinated polyethylene, glass transition temperature, (4) 623
Chlorobutyl rubber, blend with SBR, (5) 860
carbon-black-filled vulcanizates, properties, (1) 79
crosslink density determination, (5) 860
determination in vulcanizates, (1) 97
identification in blends, (4) 631, 653
radiation curing of, (5) 860
structure of, (5) 860
swelling in cyclohexane, (5) 860
Chlorosulfonated polethylene, degradation and ir identification, (2) 289
identification in blends, (4) 640
Chromatography, thin-layer, of styrene–butadiene copolymers, (2) 343
of urethane foam pyrolysis products, (2) 343
Cleavage, of crosslinks, kinetics, (5) 913
of main chain, kinetics, (5) 913
Comb polymers, as models for branching, (5) 1035
Combustion, of hydrocarbon elastomers, (1) 124
of polychloroprene, foam, (1) 132
of polyurethanes, (2) 343
of SBR latex foam, (1) 124
of various elastomers, (1) 124, (2) 340
products, physiological response to, (2) 343
Compatibility, of polymer mixtures, (2) 218
of polystyrene–poly(vinyl methyl ether), (2) 218
Configuration, of polymer molecules, (3) 513
random, (3) 513
Conformational energy, in rubberlike elasticity theory, (3) 495
Conveyor belt, see Belt
Copolymers, alternating, of butadiene with acrylonitrile and deuterated analogs, (4) 719
Copolymers, analysis of, by ^{13}C NMR, (4) 705
Cord, see Tire cord
Corona, test apparatus, (2) 353
Correlation, intermolecular and intramolecular, (3) 513
molecular order defined by, (3) 513
Coupling agents, see also Promoters
effect on bound rubber, (3) 410
effect on mechanical properties of vulcanizates, (3) 410
for silica–rubber systems, (3) 410
titanate, for fillers in polymers, (5) 1091
Crack growth, and abrasion, (5) 902
in rubbers, (5) 902
mechanism in nylon, (3) 445
Crazing, effect of nitrogen on, (3) 445
of prestrained rubber at low temperature, (3) 445
Creep, equations for, (2) 154
long-time, of natural rubber vulcanizates, (2) 154
of natural rubber vulcanizates, effect of humidity and oxygen on, (2) 154
Crepe hardening of silicone rubber, (4) 558
Crosslink density, determination, (5) 795, 860
effect of radiation dose on, (2) 141
effect of silica on, (5) 795
effect of stretching on, (5) 1004
of filled polyacrylate, (5) 845
of natural rubber, (2) 141
of radiation-cured rubbers, (5) 860
Crosslinking and rubber elasticity theory, (3) 495
by peroxide, promotion by *s*-triazines, (5) 878
by radiation, (5) 860, 878
effect on viscoelastic properties, (5) 981
in sulfur vulcanization, (5) 889
of fluorosilicone rubber, (5) 944
of polybutadiene under strain, (5) 1004
of terminally unsaturated BR with polyamines, (2) 202
Crosslinks, disulfide in EPDM, (5) 889
effect of stretching on, (5) 902
effect on tearing energy, (5) 902
entanglements as, (2) 164
functionality of, effect on network properties, (5) 1008
in 1,2-polybutadiene, (2) 164
in states of strain, (2) 164
polysulfide in natural rubber, (2) 141
scission in natural rubber, (2) 141
thermal cleavage, (5) 913
types in natural rubber, (2) 141
Crystallization, of biaxially stretched rubber, (5) 1093
CTAB specific surface, of carbon black, (4) 538
Curie-point pyrolysis–gas-chromatography, determination of polymeric constituents in vulcanizates, (1) 97
Curing, see Crosslinking
Cut growth, effect of carbon black on, (5) 1090
Cyclododecatriene, dithiol adducts as radiation-curing promoters, (5) 860
reaction with dithiols, (5) 860
N-Cyclohexylthiophthalimide, as scorch inhibitor, (5) 1108
mechanisms of prevulcanization inhibition, (4) 790

Degradation, of polybutadiene, (4) 692
of vulcanizates by boiling in 1,2-dichlorobenzene, (2) 289
of vulcanizates for ir identification, (2) 289

Dehydroisodicyclopentadiene, in EPDM, (4) 747
Depolymerization of scrap rubber, (1) 50
Depolymerized scrap rubber, antioxidant activity of, (1) 62
as compounding ingredient, (1) 50
as fuel oil extender, (1) 50
as stabilizer for solution rubber, (1) 62
Determination of polymer constituents in rubber vulcanizates, (1) 97, (2) 310, (4) 631, 640, 653, 661
Deuterated elastomers, (4) 719
p,p-Diaminodiphenylmethane, complexes of, as curing agents for polyurethanes, (5) 1102
salt complexes of, synthesis and properties, (5) 1102
Dibutyl phthalate adsorption of carbon black, (4) 538
Differential scanning calorimetry, see also Thermal analysis
for identification of rubbers in blends, (2) 301, (4) 631, 640, 653
for T_g of chlorinated polyethylene, (4) 623
in analysis of vulcanization, (1) 26
of NBR, (4) 678
of tread and sidewall stocks, (2) 301, (4) 631, 640, 653
use in analyzing vulcanizates, (4) 661
Differential thermogravimetry, see also Thermal analysis
for identification of compounding components, (4) 661
for identification of rubbers in blends, (4) 631, 640, 653
Diffusion, in polymers, as detected by ESR, (5) 1078
of benzene in polystyrene–poly(vinyl methyl ether) films, (2) 218
Dihydromyrcene, see 2,6-Dimethyl-2-*cis*-6-octadiene
Diisocyanates, synthesis and use, (3) G70, G75
1,6-Diisocyanatohexane, synthesis, G73
1,5-Diisocyanatonaphthalene, mentioned, (3) G73
1,8-Diisocyanatooctane, synthesis, G73
Dilatometry, glass transition temperature of chlorinated polyethylene, (4) 623
Dilute solutions, of rubber, excluded volume effect in, (4) 765
of *trans*-poly pentenamer, (4) 781
Dimensional changes, in NBR on molding, (2) 236
2,6-Dimethyl-2–*cis*-6-octadiene, NMR of, (5) 953
oxidation, (5) 953
oxidation products, (5) 953
Dimethyldithiocarbamate salts in radiation curing, (5) 860
N,N'-Dioctyl-*p*-phenylenediamine as antiozonant in natural rubber, (1) 41
Dispersion, as step in mixing process, (3) 462
degree of, determination, (3) 462
dependence on mixer speed, (3) 462
effect on physical properties, (3) 462
Disposal of scrap tires, (1) 50
Disulfide crosslinks, in EPDM, (5) 889
Dithiols, in radiation curing, (5) 860
1,12-Dodecanedithiol, in radiation curing, (5) 860
Dynamic electrical properties, of carbon black vulcanizates, (1) 79
Dynamic modulus, of dilute solutions and long-chain branching, (5) 1035
of rubber networks, (5) 981
Dynamic properties, effect of heat treatment, (3) 410
effect of promoters, (3) 410
of carbon-black-filled oil-extended SBR, (4) 592
of carbon-black-reinforced vulcanizates, (1) 79, 89
of elastomer blends, (1) 89

Elastic energy, stored in rubbers, (5) 902
Elasticity, see also Rubber elasticity
of uncrosslinked rubbers, (5) 995
Electrical properties, of carbon-black-filled vulcanizates, (1) 79, 89
of EPM-based compositions, (2) 351, 354
of thermosetting elastomers in automotive wiring, (2) 353
Electrical resistivity, see Resistivity
Electrochemical treeing, in EPM compounds, (2) 353
Electron microscopy, image analysis of carbon black, (4) 538
Electron spin resonance, detection of free radicals, (3) 445
for study of motion in polymers, (5) 1078
study of bond rupture by, (3) 445
study of carbon black by, (3) 445
study of filled rubber by, (3) 445
Emulsion polymerization, MW regulation with blends of mercaptans, (4) 728
Encapsulation, of compounding ingredients, (5) 1093
Energetic contribution to rubber elasticity, (5) 1018
Energy, balance, in internal mixers, (3) 624
of fracture of rubber, (3) 445
of mixing, (3) 462
Entanglements, chain, (2) 164
effect on crosslink density, (5) 913
in model polystyrene networks, (2) 194
networks in 1,2-polybutadiene, (2) 164, (5) 1004
trapped, (2) 164
Entropy, contribution to rubber elasticity, (5) 1018
Epoxide, formation in oxidation of polyisoprene, (5) 953
β-(3,4-Epoxycyclohexyl)ethyltrimethoxysilane, surface treatment of glass by, (5) 819

Equivalence principle, in deformation of filled and gum rubber compounds, (4) 592
Ethyl acrylate, photopolymerization, (5) 819
Ethylene glycol dimethacrylate, as crosslinking agent for poly(ethyl acrylate), (5) 819, 830, 845
Ethylene propylene diene rubber (EPDM), see also Ethylene propylene rubber
blend with polyurethane scrap, (5) 972
characterization by ^{13}C NMR, (4) 705
chemorheology, (5) 913
cleavage of crosslinks and main chains, (5) 913
determination of, in vulcanizates, (1) 97
dynamic properties, (1) 79
effect of double-bond content, (5) 889
fast curing, (4) 747
filled with glass beads, fracture, (3) 445
for electrical application, (2) 354
in blends, dynamic properties, (1) 89
in white sidewall stocks, identification, (4) 631, 653
long-chain branching, (5) 1035
stress relaxation, (5) 913
sulfur vulcanization, (5) 889
thermal analysis of, (4) 661
thermal degradation, (5) 913
vulcanization kinetics, (5) 889
Ethylene propylene rubber (EPM), and surface-modified carbon black, (3) 410
and theory of rubber elasticity, (3) 495
degradation and ir identification, (2) 289
dielectric properties, (2) 351
effect of silica filler, (5) 795
electrochemical treeing in, (2) 353
in insulation of power cables, (2) 351
long-chain branching, (5) 1035
promoted peroxide cure, (5) 878
promoted radiation cure, (5) 878
Ethylene propylene triene copolymers, preparation and properties, (4) 747
Ethylene–(vinyl acetate) copolymer, degradation and ir identification, (2) 289
promoted peroxide cure, (5) 878
promoted radiation cure, (5) 878
Excluded volume, in rubber elasticity theory, (3) 495
Extruded rubber, microwave vulcanization, (5) 1100
Extruder processing of powdered rubber, (5) 1098
Extrusion, die swell, (4) 577
of black-filled NBR, (4) 615

Failure, in rapid sinusoidal flexing, (2) 357
of rubbers, theory, (5) 902
tensile, of rubbers, (5) 902
Fatigue, effect of carbon black on, (5) 1090
of rubbers, (5) 902
Fatty acids, tallow, use in rubber, (2) 348
Fiber–rubber composites, properties, (5) 1108
Filler, adsorption of rubber on, (5) 810
coupling agents for, (5) 1091
reinforcement, (5) 795, 819, 830, 845
rice-hull ash as, (2) 271
starch xanthide as, (5) 1092
Flame resistance, see Flammability
Flammability, and flame-spread models, (2) 345
anomalies in polymers, (2) 344
effect of hydrated fillers, (1) 124
of carborane elastomers, (1) 14
of elastomers, (2) 340
of polyurethanes, (2) 343
Flexing, failure mode in rapid sinusoidal, (2) 357
Flex life, of cast polyurethane, (5) 1101
Flow curve, for hydrodynamic analysis, (3) 462
in form of power law, (3) 462
temperature dependence, (3) 462
Fluororubber, degradation and ir identification, (2) 289
Fluorosilicone rubber, heat aging, (5) 944
molecular weight distribution, (5) 944
peroxide curing, (5) 944
stress relaxation, (5) 944
Foam, polyurethane, recycling, (5) 972
Forecast, technological for rubber processing, (5) 1096
Fourier transform NMR, in analysis of polypentenamer, (2) 329
Fractionation, of SBR by thin-layer chromatography, (2) 310
Fracture of rubber, at low temperature, (3) 445
bond rupture and, (3) 445
energy of, (3) 445
free radicals in, (3) 445
gas evolution in, (3) 445
Griffith criterion, (3) 445
in presence of filler, (3) 445
mechanics, (5) 902
Free radicals, decay of, (3) 445
detection by ESR, (3) 445
in polyisoprene oxidation, (5) 953
in prestrained rubber, (3) 445
produced by fracture of rubber, (3) 445
reaction with oxygen, (3) 445
stable, as ESR spin labels, (5) 1078
Friction on ice, of rubber vulcanizates, (4) 527

Gamma radiation, crosslinking of BR in states of strain, (2) 164
Gas chromatography, of urethane foam pyrolysis products, (2) 343
use in oxidation studies, (4) 692
Gaskets, high performance, (1) 14
Gas–liquid chromatography on polymers, polyisobutylene–hydrocarbons, (1), 108 119
temperature coefficients, (1) 108, 119

Gaussian chains, in entanglement networks, (5) 1004
in rubber elasticity theory, (5) 1018
Gel-permeation chromatography, of block copolymer, (3) 359
of polybutadiene, (2) 310, (3) 359
of polyisoprene, (3) 359
of polystyrene, (2) 310, (3) 359
of SBR, (2) 310
technique, (3) 359
Glass, adhesion of surface-treated, to polyacrylate, (5) 810, 819, 830
surface treatment of, (5) 810, 819, 830
Glass spheres, as fillers for polyacrylate, (5) 810, 819, 830
distribution in rubber, (5) 819
size fractionation, (5) 810
surface-treated, (5) 810, 819, 830
surface treatment of, (5) 810
Glass transition temperature, and decay rate of free radicals, (3) 445
of chlorinated polyethylene, (4) 623
of rubber on carbon black surface, (3) 410
of SBR–BR blends, (2) 301
release of sorbed gas at, (3) 445
strain dependence of, (4) 623
use in identification of blend components, (4) 631, 640, 653
Gradient elution technique, in thin-layer chromatography, (2) 310
Graphitized carbon black, and bound rubber, (4) 548
in silicone rubber, (4) 558
Guide for authors, (1) G27, (3) G62
Gutta-percha, oxidative degradation, (5) 913

Hardness, effect of heat-treating masterbatch on, (3) 410
effect of promoter, (3) 410
effect of surface oxidation of carbon black, (3) 410
of silica–rubber system, (3) 410
Heat aging, and chemorheology, (5) 913
of fluorosilicone, (5) 944
Heat of vulcanization, (1) 26
Heat resistance, of carborane elastomers, (1) 14
Heat transfer coefficients, rubber-to-steel-to-water, (3) 462
Heat treatment, effect on vulcanizate properties, (3) 410
of carbon-black–rubber mixtures, (3) 410
of silica–rubber mixtures, (3) 410
Hexafluoropropylene–vinylidene fluoride copolymer, see Fluororubber
Hexamethylenetetramine adducts, of phenol, as adhesion promoters for fabric, cord, and wire, (5) 1103
of resorcinol, as adhesion promoters for wire cord, (2) 346
High-temperature performance, of various oil resistant elastomers, (2) 356
Hose, automated production, (5) 1096
design for unusual application, (5) 1095
dispersions in manufacture of, (5) 1093
European and American technology, (5) 1094
manufacture, compounding technique, (5) 1094
thermoplastic, for high pressure, (5) 1095
Humidity, effect on creep of NR gum vulcanizates, (2) 154
Hydrated fillers, for reducing smoke generation, (1) 124, 132
Hydrogen sulfide, addition to allene, (5) 860
addition to polyolefin, (5) 860
reaction with trivinylcyclohexane, (5) 860
Hydroperoxide, formation in oxidation of polyisoprene, (5) 953
Hysteresis, and reinforcement, (3) 410
and treadwear, (3) 410
dynamic, equivalence principle for, (4) 592
effect of carbon black properties on, (3) 410
effect on failure, (5) 902
of silica–rubber systems, (3) 410

Identification of elastomers in vulcanizates, by ^{13}C NMR, (4) 705
by degradation and ir, (2) 289
by total thermal analysis, (2) 301, (4) 631, 640, 653, 661
Image analysis, of electron micrographs, (4) 538
of silica, (4) 558
Infrared spectroscopy, end group determination by, (3) 445
Fourier transform, (2) 348
in oxidation study, (4) 692
of alternating copolymers, (4) 719
of rubber surface, (1) 41
of vulcanizate combustion products, (2) 340
polymer identification by degradation of vulcanizates and, (2) 289
study of BR vulcanization, (2) 348
Injection molding, compounding for, (2) 263
in multistation machines, (2) 263
machine, operating variables, (5) 1108
of black-filled NBR, (4) 615
of polyurethanes, (5) 1103
of silicone rubber powder, (2) 337
simulation by capillary rheometer, (2) 355
Internal mixers, analysis of, (3) 462
dimensions of, (3) 462
energy consumption in, (3) 462
flow in, (3) 462
power consumption, (5) 1099
practical parameters for, (4) 577
processing conditions in, (3) 462
process variables, (3) 462
scale-up criteria, (3) 462
use in carbon-black–SBR, (4) 548
Irradiation, see Radiation
Isobutylene–cyclopentadiene copolymers synthesis, (5) 1105
vulcanizate properties, (5) 1105

Isobutylene–isoprene copolymers, high-unsaturation, synthesis, (5) 1105
vulcanizate properties, (5) 1106
Isocyanate, determination of unreacted groups, (2) 194
Isoprene, reaction with *t*-butyllithium, (5) 1070

Kaolin, effect on peroxide cure, (5) 878
Kinetic studies, of modifiers in emulsion polymerization, (4) 728

Latexes, high solids, preparation of, (4) 728
Latex foam, combustion of, (1) 124
smoke inhibition in, (1) 124
Light scattering, disymmetry, of carbon black, (4) 538
of butyl rubber solution, (4) 765
Linear homopolymers in dilute solution, two-parameter theory, (4) 765
Liquid elastomer, casting, (5) 1111
cast, properties and applications, (5) 1111, 1112
oil requirements for, (2) 346
terminally brominated polybutadiene, (2) 202
Lithium alkyl, see Alkyllithium and Organolithium
Loops, in polystyrene networks, (2) 194
Low temperature properties, of carborane elastomers, (1) 14

Magnesium hydroxide, for smoke inhibition, (1) 124
Master batch, in mixing, (3) 462
Master curve, viscoelastic, (1) 69, (5) 981
Mastication of carbon-black–SBR stocks, (4) 548
Mercaptans, blends of, as modifiers in emulsion polymerization, (4) 728
Mercaptobenzothiazole, derivatives in radiation curing, (5) 860
zinc salt in sulfur vulcanization, (5) 889
2-Mercaptoimidazoline, in vulcanization of polychloroprene, (1) 19
Metal oxides in vulcanization of polychloroprene, (1) 19
Methacryloxypropyltrimethoxysilane, as coupling agent for EPM, (5) 795
surface treatment of glass by, (5) 819
Metric system of units, conversion factors, (3) G61, (4) G94, (5) G102
usage, (1) 1
Microcracks, growth mechanisms in strained rubber, (3) 445
Microscopy, of filler aggregates, (3) 462
of fracture surfaces, (3) 445
Microstructure of depolymerized rubber, (1) 50
Microwave, heating in manufacture of conveyor belting, (5) 1098
vulcanization of extrudates, (5) 1100
Mill processing, of powdered rubber, (2) 254
Mixer, see Internal mixers

Mixing, and degree of dispersion, (3) 462
computer modeling of, (3) 462
control by power integrator, (5) 1099
effect of bound rubber on, (4) 548
effect of compound variables, (3) 462
effect of operating variables, (3) 462
high-shear, practical parameters for, (4) 577
in internal mixers, (3) 462
mechanism of, (3) 462
of rubber compounds, scale-up, (4) 577
practical parameters for, in Banbury, (4) 577
Modifiers, blends of mercaptans as, in emulsion polymerization, (4) 728
Modulus, bulk, tester, (2) 246
effect of heat treating carbon black on, (3) 410
effect of heat treating masterbatch on, (3) 410
effect of promoters on, (3) 410
of elasticity, effect of dilution, (3) 513
of silica–rubber systems, (3) 410
of swollen poly(dimethylsiloxane) networks, (2) 186
of swollen polystyrene networks, (2) 194
Molding, with multistation injection machines, (2) 263
Molecular conformation, of polypentenamer, (4) 781
Molecular dimensions, direct measurement, (3) 513
of polypentenamer, (4) 781
Molecular motion, and structure, in chlorinated polyethylene, (4) 623
effect of solvent, by ESR, (5) 1078
in polymers by ESR, (5) 1078
Molecular weight, of depolymerized rubber, (1) 50
of polypentenamer, (4) 781
of soluble rubber in carbon black compounds, (4) 548
regulation in emulsion polymerization, (4) 728
Molecular weight distribution, and rubber elasticity theory, (3) 495
effect of bound rubber, (4) 548, (5) 810
effect on long-chain branching determination, (5) 1035
obtained in anionic polymerization, (3) 359
of SBR by thin-layer chromatography, (2) 310
of various polymers by GPC, (2) 310
Poisson distribution, (3) 359
Mooney–Rivlin equation, C_1 and C_2 constants (review), (3) 495
C_2 constant for poly(dimethylsiloxane) networks, (2) 176
for entanglement networks, (5) 1004
Mooney rheometer, variable-speed, (1) 69
Morphology, of powdered rubber, effect on processing, (2) 254
of rice-hull ash, (2) 271

Natural rubber (NR), abrasion and crack growth, (5) 902
and theory of rubber elasticity, (3) 495, 513
Banbury mixing time, (3) 410
bound rubber on carbon black, (5) 795
carbon black effects on bulk and Young's modulus, (2) 246
–carbon-black mix, heat treatment, (3) 410
chemorheology, (2) 141, 154
crosslink density and entanglements, (5) 913
crosslinks in, (2) 141
degradation and ir identification, (2) 289
dynamic hysteresis of, (4) 592
effect of reinforcement promoters, (3) 410
fracture, ESR study, (3) 445
friction on ice, (4) 527
identification in sidewall compounds, (4) 631, 653
isomerized, abrasion, (5) 902
long-time creep of vulcanizates, (2) 154
peroxide-cured, stress relaxation, (2) 141
radiation-cured, stress relaxation, (2) 141
radiation, curing of, (5) 860
reinforcement by silica, (3) 410
relaxation-time distribution, (5) 981
strained sample, x-ray diffraction, (3) 445
stress relaxation, (2) 141, (5) 913
stress relaxation mechanisms, (2) 141
stress–temperature coefficient, (5) 1018
swelling in cyclohexane, (5) 860
thermal chain cleavage, (5) 913
thermal stability of vulcanizates, (2) 141, 154
thermoelasticity, (3) 513, (5) 1018
vulcanization, heat of, (1) 26
Neoprene, see Polychloroprene
Networks, closed-loop defects, (2) 194
entanglement, (2) 164
from terminally brominated BR, (2) 203
model polystyrene, (2) 194
of molecular entanglements, (5) 1004
of random coils, theory, (5) 1008
poly(dimethylsiloxane), in compression, (2) 176
theory, (2) 164
uniform, polyisoprene, (5) 1104
viscoelasticity of, (5) 981
Nitrile rubber (NBR), (3) G73
alternating copolymer, (4) 719
anisotropy of molded vulcanizates, (2) 236
blend with polyurethane scrap, (5) 972
capillary rheometry, (4) 615
carbon black compounds, effect of heat treatment, (3) 410
carbon-black-filled vulcanizates, dynamic mechanical properties, (1) 79
carboxyl-terminated, (5) 1111
containing copolymerized antioxidants, (2) 337
fracture, ESR study, (3) 445
friction on ice, (4) 527
ozone stress cracking, (3) 445
powdered, processing, (2) 254, (5) 1098
rheological studies, (1) 69
thermal degradation of, (4) 678
use in hose manufacture, (5) 1094
vulcanizates, degradation and ir identification, (2) 289
x-ray diffraction under strain, (3) 445
Nitroxides, as ESR spin labels, (5) 1078
chemical attachment to polymers, (5) 1078
diffusion in rubber, (5) 1078
Normal stress, effect of mixing, (3) 462
in internal mixer, (3) 462
Nuclear magnetic resonance (NMR), ^{13}C, for characterizing elastomer structure, (4) 705
^{13}C spectra of polypentenamer, (2) 329
^{13}C spectra of SBR, (5) 1044, 1055
for elastomer structure determination, (5) 1109
monomer sequence of SBR, (5) 1055
of oxidation of polyisoprene, (5) 953
of polyisoprene, (5) 953
relaxation studies, (5) 1109
spectra of polyalkenyllithium compounds, (3) 359
spin–lattice relaxation for polystyrene–poly(vinyl methyl ether), (2) 218
study of carbon-black-filled rubber, (5) 1109
study of high-*cis* polyisoprene, (5) 1110
Nylon, chain scission by fracture, (3) 445
cord in radial tires, (5) 1094
crack growth mechanism, (3) 445
reinforcement for hose, (5) 1095

Occluded rubber, (3) 410
Oil, extender, effect of combined sulfur in, (5) 1092
effect of, on friction of rubber on ice, (4) 527
extract of depolymerized scrap rubber, (1) 50
in liquid rubbers, (2) 346
Oil resistance, of elastomers and service temperature, (2) 356
Optical anisotropy, of chain molecule, (3) 513
Organolithium compounds, see also Butyllithium
analysis, (3) 359
as polymerization initiators, (3) 359, (5) 1070
association states, (3) 359
in anionic polymerization (review), (3) 359
preparation and purification, (3) 359
Orientation, molecular, and fracture mechanics, (3) 445
and rubber elasticity theory, (3) 495
O-rings, high-performance, (1) 14
Oxidation, and stress relaxation, (5) 913
degradative, of NR vulcanizates, (2) 141, 154
mechanism for polyisoprene, (5) 953

of polyisoprene, NMR study, (5) 953
stability of radiation, and peroxide-cured rubbers, (5) 878
thermal, of BR, (4) 692
Oxygen, effect on creep in gum vulcanizates, (2) 154
Ozone, attack on natural rubber vulcanizates, (1) 41

Particle size, of ground rice-hull ash, (2) 271
of powdered rubber, effect on processing, (2) 254
Pentachlorothiophenol, in depolymerization of rubber, (1) 50
Permanent set, see Set
Peroxide, cure of carborane elastomers, (1) 14
cure of natural rubber, (2) 141
cure of NBR, (2) 236
cure, promoted by *s*-triazine derivatives, (5) 878
cure, promoted by triallylcyanurate, (5) 878
degradation of polystyrene, (5) 913
formation during oxidation of polyisoprene, (5) 953
Phase separation, in polystyrene–poly(vinyl methyl ether) systems, (2) 218
Phenol adduct of hexamethylenetetramine, see Hexamethylenetetramine
Phenotropins, see hexamethylenetetramine adducts
Photooxidation of polybutadiene, mechanism of, (4) 692
Phthalimides, (*N*-substituted thio), as scorch inhibitors, (4) 790
Poisson ratio, effect of carbon black on, (2) 246
of elastomers, (2) 246
Polyacrylate, adhesion to glass, (5) 819, 830, 845
degradation and ir identification, (2) 289
physical properties of reinforced, (5) 830
reinforced with glass beads, (5) 819, 830, 845
reinforcement of, (5) 819, 930, 845
swelling of reinforced, (5) 845
Polyacrylonitrile, narrow MW distribution, (3) 359
Poly(*n*-alkyliminoalanes), as stereospecific catalysts for isoprene, (4) 736
Polybutadiene (BR), and rubber elasticity theory, (3) 495
blends with SBR, abrasion resistance, (2) 356
bromine-terminated, (2) 203, (3) 410
by anionic polymerization, (3) 359
carbon-black-filled vulcanizates, bulk and Young's modulus, (2) 246
carbon-black-filled vulcanizates, dynamic mechanical properties, (1) 79
characterization by ^{13}C NMR, (4) 705
compounds, thermal analysis of, (4) 661
degradation and ir identification, (2) 289
effect of carbon-black surface properties, (3) 359
effect of polymerization conditions on microstructure, (3) 359
fracture, EPR study, (3) 445
friction on ice, (4) 527
grafting to carbon black, (3) 359
identification of in blends, (2) 301, (4) 640, 653
liquid rubber, (3) 410
low MW, (3) 359
mixing parameters for, (4) 577
MW and MW distribution, (3) 359
NMR of oligomer, (3) 359
oil-extended, processing of, (4) 577
oxidation of, (4) 692
photooxidation of, (4) 692
radiation curing, (5) 860
relaxation-time distribution, (5) 981
trans, structure of, (4) 719
vulcanization, ir study, (2) 348
1,2-Polybutadiene, crosslinking, (2) 164
crosslinked under strain, (2) 164, (5) 1004
entanglement networks in, (2) 164, (5) 1004
intrinsic viscosity–MW relation, (2) 164
stress–strain of vulcanizates, (2) 164
Poly(*t*-butyl crotonate), narrow MW distribution, (3) 359
Poly(*n*-butyl isocyanate), narrow MW distribution, (3) 359
Poly(*p*-*t*-butylstyrene), narrow MW distribution, (3) 359
Polychloroprene, blend with scrap polyurethane, (5) 972
carbon black effect on bulk and Young's modulus, (2) 246
carbon-black-filled vulcanizates, dynamic mechanical properties, (1) 79
degradation and ir identification, (2) 289
flame resistance, (1) 132, (2) 340
identification in blends, (4) 640
powdered, processing of, (5) 1098
smoke and heat generation, (1) 132
vulcanization, (1) 19
Polydiene rubbers, radiation curing of, (5) 860
Poly(2,3-dimethylbutadiene), (3) G73
chain-end structure, (3) 359
NMR of oligomer, (3) 359
Poly(dimethylsiloxane), and theory of rubber elasticity, (3) 495
concentrated solution behavior, (3) 513
degradation and ir identification, (2) 289
effect of silica filler, (5) 795
fracture, ESR study, (3) 445
macrocyclization equilibrium, (3) 513
narrow MW distribution, (3) 380
stress–strain isotherm, (2) 176
stress–temperature coefficient, (2) 176, (3) 513
X-ray diffraction under strain, (3) 445
Polyester, cord in radial tires, (5) 1094

fabric as reinforcement for conveyor belt, (5) 1092
hydroxyl-terminated, (3) G73
Polyethers, (3) G73
Poly(ethyl acrylate), see also Polyacrylate
crosslinked with ethylene glycol dimethacrylate, (5) 819, 830, 845
reinforcement by glass spheres, (5) 819, 830, 845
swelling in chlorobenzene, (5) 845
Polyethylene, promotion of peroxide cure, (5) 878
promotion of radiation cure, (5) 878
stress–temperature coefficient, (3) 513
thermoelasticity, effect of dilution, (3) 513
Poly(ethylene terephthalate), peroxy radicals in, (3) 445
Poly(2,4-hexadiene), chain-end structure, (3) 359
Polyisobutylene, see also Butyl rubber
and theory of rubber elasticity, (3) 513
concentrated solution behavior, (3) 513
elasticity of uncrosslinked, (5) 995
gas–liquid chromatography, (1) 108, 119
interaction with carbon black, (3) 410
interaction with hydrocarbons, (1) 108, 119
stress relaxation of uncrosslinked, (5) 995
stress–temperature coefficient, (3) 513
thermal analysis, (4) 661
Polyisoprene, carbon-black-filled, bulk and Young's modulus, (2) 246
carbon-black-filled, dynamic mechanical properties, (1) 79
chain-end structure, (3) 359
characterization by ^{13}C NMR, (4) 705
cis-1,4 content, (3) 359
crystallization on biaxial extension, (5) 1093
determination in vulcanizates, (1) 97
elasticity of uncrosslinked, (5) 995
filled with glass beads, silica, NaCl, (3) 445
grafted to carbon black, (3) 410
high-*cis*, synthesis of, (4) 736
hydroxy-terminated, (5) 1104
narrow MW distribution, (3) 359
NMR of, (5) 953, 1110
NMR of oligomer, (3) 359
oxidation of, (5) 953
stereospecific, synthesis of, (4) 736
stress relaxation of uncrosslinked, (5) 995
thermal analysis of, (4) 661
uniform networks, synthesis and properties, (5) 1104
via butyllithium initiation, (5) 1070
Polymer–filler interaction, for polyacrylate–glass, (5) 819, 830, 845
in silica-filled vulcanizates, (5) 795
Polymerization, anionic, see Anionic polymerization
Polymerization catalysts, alanes as, (4) 736
stereospecific, (4) 736
Polymer–solvent interactions, in concentrated solution, (1) 108, 119
Poly(methyl methacrylate), and rubber elasticity theory, (3) 495
deuterated, neutron scattering, (3) 513
molecular motion by ESR, (5) 1078
narrow MW distribution, (3) 359
Poly(α-methylstyrene), narrow MW distribution, (3) 359
Polypentadiene, chain-end structure, (3) 359
Polypentenamer, ^{13}C NMR analysis of, (4) 705
degradation and ir identification, (2) 289
dilute solution properties of, (4) 781
isomer determination by NMR, (2) 329
Poly(propylene sulfide), narrow MW distribution, (3) 359
Polystyrene, (3) G73
blends with poly(vinyl methyl ether), (2) 218
by butyllithium initiation, (5) 1070
carboxyl terminated, Ag salt, (3) 513
chloromethyl-substituted, (2) 194
compatibility with poly(vinyl methyl ether), (2) 218
degradation by peroxide, (5) 913
deuterated, neutron scattering, (3) 513
dynamic moduli, (E) 981
grafted to carbon black, (3) 410
highest MW, (3) 359
isocyanate-substituted, (2) 194
model networks, (2) 194
molecular motion by ESR, (5) 1078
MW distribution of anionic, (5) 1070
narrow MW distribution, (3) 359
stress relaxation and degradation, (5) 913
stress–temperature coefficient, (3) 513
Polysulfide crosslinks, in EPDM, (5) 889
Poly(trifluoropropylmethyl) siloxane, see Fluorosilicone rubber
Polyurethane, blends with powdered scrap, (5) 972
chemistry, (3) G70, G73
cure with complexes of methylene dianiline, (5) 1102
decomposition products, irritation by, (2) 343
degraded, (5) 972
flexible foam, pyrolysis, (2) 343
flex requirements and testing, (5) 1101
foam, (3) G73
for composite tire, (5) 1093
injection molding of, (5) 1103
moisture resistance improvement, (2) 348
oil-extended, (2) 346
scrap, utilization of, (5) 972
thermoplastic, uv stabilization, (5) 1101
thermosetting, utilization of scrap, (5) 972
Poly(vinyl chloride), (3) G73
Poly(vinyl methyl ether), compatibility with polystyrene, (2) 218
Powdered, polymers, manufacture and use of, (5) 1099
polyurethane scrap, use of, (5) 972
rubber, continuous processing of, (5) 1098

rubber, effect of morphology and particle size in milling, (2) 254
rubber, in internal mixers, (3) 462
rubber, use of starch xanthide in, (2) 338
silicone rubber, (2) 337
Powdering, of polyurethane scrap, (5) 972
Prevulcanization, see Scorch
Processability, of carbon-black-filled rubber, effect of bound rubber on, (4) 548
Processing, see also Mixing
continuous, of powdered rubbers, (5) 1098
Promoters, see also Coupling agents
effect on bound rubber, (3) 410
for carbon-black–rubber interaction, (3) 410
for peroxide curing, (5) 878
for radiation curing, (5) 860, 878
for silica–rubber interaction, (3) 410
in reinforcement of butyl rubber, (3) 410
1,3-Propanedithiol, in radiation curing, (5) 860
zinc mercaptide of, (5) 860
1,2,3-Propanetrithiol, in radiation cure of CIIR, (5) 860
Propylene butadiene copolymer, characterization by ^{13}C NMR, (4) 705
Pyrolysis, and gas chromatography, for determination of blend constituents, (1) 97
of polychloroprene, (1) 132
of vulcanizates for ir identification, (2) 289

Quality control, in compounding, by thermal analysis, (4) 661

Radiation crosslinking, effect of dose on crosslink density, (2) 141
in state of strain, (2) 164
of chlorobutyl rubber, (5) 860
of natural rubber, (2) 141
of 1,2-polybutadiene, (2) 164
of polydiene rubbers, (5) 860
of poly(dimethylsiloxane), (2) 176, 186
promotion by polythiols, (5) 860
promotion by triallylcyanurate, (5) 878
promotion by *s*-triazine derivatives, (5) 878
technology and economics, (5) 1100
vessel for, (2) 164
Reclaimed rubber, stabilizing activity, (1) 62
Recovery, of uncrosslinked rubbers, (5) 995
Recycling, of scrap tires, to make tackifying resin replacements, (2) 338
Reinforcement, and bound rubber, (3) 410, (5) 810
and tear strength, (3) 410
and tread wear, (3) 410
by carbon black, effect on Poisson ratio, (2) 246
by glass spheres, (5) 819, 830, 845
by nylon 66 fiber, (5) 1094
by polyester fabric, (5) 1092
by powdered silicone rubber, (2) 337
by rice-hull ash in SBR, (2) 271
by short cellulose fibers, (5) 1108
by silica, (5) 795
by surface interaction, (3) 410
chain breakage mechanism, (3) 410
definition, (3) 410
effect of carbon black structure, (4) 538
effect of filler properties on, (5) 795, 819
effect of filler surface on, (5) 795, 819, 830, 845
historical background, (3) 410
hydrodynamic theory, (3) 410
in terminally brominated BR, (2) 203
mechanisms, (3) 410
molecular slippage mechanism, (3) 410
of polyacrylate rubber, (5) 819, 830, 845
of silicone, by treated silica, (4) 558
promotion by coupling agents, (3) 410
theory of, (5) 819, 830, 845
Relaxation, of polymers, NMR studies, (5) 1109
spectrum of polystyrene, (5) 913
spectrum of rubber networks, (5) 981
time distribution of vulcanizates, (5) 981
times, in polystyrene–poly(vinyl methyl ether), (2) 218
Resilience, rebound, of silica–rubber systems, (3) 410
Resin, tackifying from scrap rubber, (2) 338
Resistivity of filled rubber, (3) 410
Resorcinol, hexamethylenetetramine reaction product, (2) 346
Resotropin, see Hexamethylenetetramine adducts
Retardation of vulcanization, (5) 1108
by *N*-(substituted thio)phthalimides, (4) 790
Rheology, see also Viscoelasticity
of amorphous elastomers, (1) 69
of carbon-black-filled rubber, (4) 615
of rubber compounds, (2) 263
of rubber networks, (5) 981
study with Rheovibron, (1) 69
with capillary rheometer to simulate injection molding, (2) 355
Rice-hull ground ash, as rubber filler, (2) 271
Road wear, see Tread wear
Rubber Division, ACS, Best Papers Awards, (4) 691
bylaws, (1) G12
future meetings, (1) G5, (2) G54, (3) G58, (4) G84, (5) G98
library and information service, (1) G2, (2) G50, (3) G59, (4) G92, (5) G100
officers and executive Committee, (1) G1, (2) G49, (3) G57, (4) G83, (5) G97
policy on technical papers, (1) G26
program for fall meeting, (4) G86
program for spring meeting, (1) G7
symposia at future meetings, (1) G6, (2) G54, (3) G58, (4) G85, (5) G99
Rubber elasticity, and chemical stress relaxation, (5) 913
and entanglements, (2) 164, (5) 1004
energetic contribution to, (5) 1018

of networks formed in the swollen state, (2) 186
statistical mechanics, (5) 1008
theory of, (5) 1008, 1018
thermodynamics of, (5) 1018

Scanning electron microscope, examination of fracture surfaces, (3) 445
Scission, see Cleavage
Scorch, inhibition by *N*-(substituted thio)-phthalimides, (4) 790
inhibitors, (4) 790, (5) 1108
Scrap, of thermosetting polyurethane, (5) 972
rubber, depolymerized, (1) 62
rubber, tackifiers from, (2) 338
tires, disposal, (1) 50
Service temperatures of various oil resistant elastomers, (2) 356
Set, effect of swelling on, (5) 902
tensile, of uncrosslinked rubbers, (5) 995
tensile, of vulcanized rubbers, (5) 902
Shear strain, in internal mixer, (3) 462
parameter, for mixing rubber compounds, (4) 577
rate, in internal mixer, (3) 462
Shear stress, effect on improving dispersion, (3) 462
in internal mixer, (3) 462
Shrinkage, on molding, in NBR, (2) 236
SI units, conversion factors, (3) G61, (4) G94, (5) G102
usage, (1) 1
Sidewall, tire, component identification by thermal analysis, (2) 301
Silanes, coupling agents for EPM, (5) 795
silicas treated with, (4) 558
surface treatment of glass by, (5) 819
Silica, aggregates in, (4) 558
as filler for terminally brominated BR, (2) 202
as reinforcing agent, (3) 410
bound rubber on, (5) 810
fumed, as reinforcing filler for silicone, (4) 558
polysiloxane structure, (3) 410
reinforcement by, (5) 795
structure, effect of, (5) 795
surface area, (5) 795
surface chemistry, (3) 410
surface modification, (3) 410, (4) 558
surface treatment, (5) 795
Silica–rubber systems, abrasion resistance, (3) 410
chemical promotion, (3) 410
heat treatment, (3) 410
Silicone rubber, see also Poly(dimethylsiloxane)
as insulation for electric cables, (2) 355
degradation and ir identification, (2) 289
effect of silica filler, (5) 795
hydroxy-terminated, (4) 558
powdered, (2) 337
reinforcement by silica, (4) 558
silica-bound polymer, (5) 810
Siloxane, as surface treatment of glass, (5) 819
as surface treatment of silica, (5) 795
structure of silica, (3) 410
Skid resistance, effect of carbon black on, (5) 1091
of rubbers on ice, (4) 527
Smoke, development, theory, (2) 340
generation during combustion of rubbers, (1) 124
inhibition by hydrated fillers, (1) 124
inhibition in combustion of polychloroprene, (1) 132
physiological response to, (2) 341
Solution masterbatch of SBR and carbon black, (4) 548
Solution properties of butyl rubber, (4) 765
Solvent resistance of carborane elastomers, (1) 14
Sorption of benzene in polystyrene–poly(vinyl methyl ether), (2) 218
Sound velocity in chlorinated polyethylene, (4) 623
Specific heat of rubber mix, (3) 462
Squalene, epoxide derivative, (5) 953
NMR spectrum, (5) 953
oxidation, (5) 953
oxidation products, (5) 953
Stabilizing activity of depolymerized scrap rubber, (1) 62
Starch xanthide, in elastomer masterbatches, (5) 1092
preparation of, (5) 1092
process for powdered rubbers, (2) 338
Statistical mechanics of random coil networks, (5) 1008
Steady-shear measurements of amorphous elastomers, (1) 69
Stereospecific polymerization, with alanes and aminoalanes, (4) 736
Strain, amplification by filler, (3) 410, (4) 592
dependence of T_g, (4) 623
-dependent dynamic properties, (1) 79, 89
hardening, (3) 410
Strength of rubbers, theory, (5) 902
Stress relaxation, chemical, (2) 141, (5) 913
chemical, of EPDM vulcanizates, (5) 913
chemical, of peroxide cured NR, (5) 913
comparison with ESR results, (3) 445
effect of atmosphere on, (2) 141
of carbon-black-filled unvulcanized rubbers, (5) 995
of fluorosilicone rubber, (5) 944
of gutta-percha, (5) 913
of radiation-cured natural rubber, (2) 141
of uncrosslinked rubbers, (5) 913, 995
of vulcanizates containing hydrogenated carbon black, (3) 410
repeated, (5) 913
Stress softening, of filled vulcanizates, (3) 410
Stress–strain isotherms, in compression, (3) 495
in tension, (3) 495
of amorphous rubbers, (1) 69

of 1,2-polybutadiene, (2) 164
of poly(dimethylsiloxane), (2) 176
Stress–temperature coefficients of poly(dimethylsiloxane), (2) 176
Styrene, reaction with *t*-butyllithium, (5) 1070
Styrene–butadiene rubber (SBR), abrasion and crack growth, (5) 902
and carbon black surface properties, (3) 410
Banbury mixing time, (3) 410
blends with BR in tire treads, effect of curing temperature, (2) 356
blends with CIIR, (5) 860
carbon-black-filled, dynamic mechanical properties, (1) 79, (4) 592
carbon-bound rubber, (4) 548, (5) 810
^{13}C NMR peak assignments, (5) 1044
compositional distribution, (2) 310
degradation and ir identification, (2) 289
depolymerized scrap rubber as stabilizer for, (1) 62
determination of, in vulcanizates, (1) 97
diads by NMR, (5) 1055
effect of blends of mercaptans in preparation of, (4) 728
effect of silica filler, (5) 795
elasticity of uncrosslinked, (5) 995
entanglements, (5) 913
filled with ground rice-hull ash, (2) 271
friction on ice, (4) 527
heat treatment of compound, (3) 410
identification in tire components, (2) 301, (4) 631, 653
microstructure by NMR, (5) 1044, 1055
molecular weight distribution, (5) 810
monomer sequence in, (5) 1055
NMR spectroscopy, (4) 705, (5) 1044, 1055
oil-extended, dynamic hysteresis of, (4) 592
oil-extended, mixing of, (4) 577
powdered, with starch xanthate, (2) 338
radiation curing of, (5) 860
reinforcement promoter for, (3) 410
relaxation time distribution, (5) 981
rheological studies, (1) 69, 79, (4) 592, (5) 981
separation by thin-layer chromatography, (2) 310
silica reinforcement, (3) 410
stress relaxation of uncrosslinked, (5) 995
swelling in cyclohexane, (5) 860
thermal analysis of, (2) 301, (4) 631, 653, 661
Styrene–butadiene block copolymers, fracture study by ESR, (3) 445
Styrene–isoprene rubber, 1,4-addition, (3) 359
styrene content, (3) 359
Sulfur, combined in extender oil, (5) 1092
Sulfur crosslinks, in EPDM, (5) 889, 913
sulfur determination in, (5) 889
thermal cleavage, (5) 913
Sulfur vulcanization, accelerated, (5) 889
heat of, (1) 26
kinetics of, (5) 889
mechanism of, (5) 889
of EPDM, (5) 889
scorch inhibition in, (4) 790
Surface chemistry, effect on reinforcement, (3) 410
of fillers, (3) 410
Surface studies of rubber exposed to ozone under stress, (1) 41
Surface treatment, of glass, (5) 819, 830, 845
of silica filler, (5) 795
Swelling, and Mooney-Rivlin constants, (3) 495
and rubber elasticity theory, (2) 186, (3) 495
anisotropy, (2) 164, 236
equilibrium, modulus obtained from, (2) 164
of glass-filled polyacrylate, (5) 845
of poly(dimethylsiloxane) networks, (2) 186
Système Internationale des Unités (SI), (1) 1

Tackifier, from scrap rubber, (2) 338
new composition, (5) 1093
Tearing, effect of carbon black on, (5) 1090
energy of rubbers, (5) 902
of rubbers, (5) 902
Tear strength, effect of chemical promoters, (3) 410
effect of heat treatment, (3) 410
of filler-reinforced vulcanizates, (3) 410
of polyurethanes, (3) G73
Telechelic polymers, studies of terminally brominated polybutadiene, (2) 202
Tensile strength, of carbon-black-filled vulcanizates, (3) 410
of reinforced systems, (3) 410
of rubber–silica vulcanizates, (3) 410
Tensile stress, anisotropy of, in NBR vulcanizates, (2) 236
Terminal functionality, in terminally brominated BR, (2) 202
2,2′,4,4′-Tetrahydroxybiphenyl as vulcanization accelerator for polychloroprene, (1) 19
2,2′,4,4′-Tetrahydroxydiphenyl sulfide as vulcanization accelerators for polychloroprene, (1) 19
Tetramethylthiuram disulfide, in radiation curing, (5) 860
natural rubber cured by, (2) 141
Thermal analysis, for identification of compound and blend components, (2) 301, (4) 631, 640, 653, 661
of NBR rubbers, (4) 678
of tire components, (2) 301, (4) 631, 640, 653
of vulcanizates, (4) 661
Thermal conductivity, of steel, (3) 462
Thermal degradation, and ir identification of rubbers in vulcanizates, (2) 289

by boiling vulcanizates in 1,2-dichlorobenzene, (2) 289
of natural rubber vulcanizates, (2) 141, 154
of NBR, (4) 678
of polychloroprene foam, (1) 132
of various vulcanizates, (2) 289
Thermal shrinkage of chlorinated polyethylene, (4) 623
Thermal volatilization analysis of NBR, (4) 678
Thermoanalytical methods, in vulcanizate analysis, (1) 26
Thermodynamics of polymer solutions, activity coefficients for solvents at high dilution in polymers, (1) 108, 119
Thermoelasticity, of poly(dimethylsiloxane) networks in compression, (2) 176
Thermogravimetry, for identification of compound components, (2) 301, (4) 631, 640, 653, 661
in the analysis of vulcanizates, (4) 661
of NBR, (4) 678
of tire components, (2) 301, (4) 631, 640, 653
Theta-solvents, for butyl rubber, (4) 765
for polypentenamer, (4) 781
Thin-layer chromatography, see Chromatography
Thioetherpolythiols, from cyclododecatriene, (5) 860
from trivinylcyclohexane, (5) 860
in radiation curing, (5) 860
Tinting strength, of carbon black, (4) 538
Tire cord adhesion promoters, (2) 346, (5) 1103
Tires, effect of carbon black on, (5) 1091
effect of nylon cord properties on, (5) 1094
radial, sidewall compounding, (4) 631
solid, polyurethane-filled, (5) 1093
stocks, identification of components by thermal analysis, (2) 301, (4) 631, 640, 653
Titanate esters, as coupling agents for fillers, (5) 1091
Tolylene diisocyanate, in polyurethanes, (3) G73
Tread wear, and reinforcement, (3) 410
effect of carbon black on, (2) 339, (5) 1091
effect of curing temperature, (2) 356
effect of promoters on, (3) 410
Triallylcyanurate, as starting material in synthesis of *s*-triazine derivatives, (5) 878
promotion of peroxide cure, (5) 878
promotion of radiation cure, (5) 878
2,4,6-Triallyloxy-*s*-triazine, see Triallylcyanurate
s-Triazine derivatives, as peroxide cure promoters, (5) 878
as radiation cure promoters, (5) 878
compatibility with rubbers, (5) 878
synthesis from triallylcyanurate, (5) 878
Tricylo[5.2.1.$0^{2,6}$]deca-2,5,8-triene, in terpolymers with ethylene and propylene, (4) 747
Triphenylmethane-4,4′,4″-triisocyanate, (3) G73
Trivinylcyclohexane, adducts as radiation-cure promoter, (5) 860
reaction with dithiols, (5) 860
reaction with H_2S, (5) 860
Tubing, see Hose

Ultrafiltration, of carbon black, (4) 538
Ultraviolet, analysis of oxidized rubber, (4) 692
stabilization of polyurethane, (5) 1101
Units of measure, (1) 1
Urethane polymer, see Polyurethane

Vacuoles, in stretched, filled polyacrylate, (5) 830
in swollen, filled polyacrylate, (5) 845
Viscoelasticity, linear and nonlinear, (5) 981
mechanisms of, (5) 981
of rubber networks, (5) 981
Rouse theory, (5) 981
Viscoelastic properties, as affected by chemical reaction, (5) 913
long-chain branching from, (5) 1035
of raw rubbers, mastercurve for, (1) 69
Viscosimetric characterization, of polypentenamer, (4) 781
Viscosity, in mixing rubber compounds, (3) 462
intrinsic–MW relation for 1,2-polybutadiene, (2) 164
of silica–rubber systems, (3) 410
temperature dependence, (3) 462
work index, in mixing of rubber compounds, (4) 577
Vulcanization, see also Crosslinking
analysis, by DSC, (1) 26
heat of, (1) 26
of BR, ir study, (2) 348
of carborane elastomers, (1) 14
of natural rubber by various means, (2) 141
of polychloroprene, accelerators for, (1) 19
of polychloroprene, effect of metal oxides, (1) 19
test for uniformity, (5) 1113

Whiting, effect on peroxide cure, (5) 878
Wire, see also Cable
automotive, (2) 353
EPDM's for, (2) 354
solid dielectric, elastomers in, (2) 350
WLF Transform, use in friction studies, (4) 527

X-ray diffraction, of alternating copolymers, (4) 719
of amorphous polymers, (3) 513
of MPC black, (3) 410
of strained rubbers, (3) 445

Zinc oxide, in sulfur vulcanization, (5) 889
Zinc sulfide, in sulfur vulcanization, (5) 889